


DIN 2510 L/NF

Svorni vijak sa reduciranim
tijelom i dvije matice
Double end studs with reduced
shank with 2 hexagon nuts
Schraubenbolzen mit Dehnschaft und
2 Sechskantmuttern



Ck35+Ck35 Fe

P	1,75	2	2,5	3	3	3,5
d2	8,5	12	15	18	20,5	23
b	20	23	28	32	35	39
m	12	16	20	24	27	30
s	22	27	32	36	41	46
l/d1	M 12	M 16	M 20	M 24	M 27	M 30
65	o					
70	o					
75	o	o				
80		o				
85		o				
90		o				
95		o				
100		o	o			
110			o	o		
120			o	o		
130			o	o	o	
140			o	o	o	
150				o	o	
160					o	o
180						o

24CrMo5+Ck35 Fe

P	1,75	2	2,5	3	3	3,5
d2	8,5	12	15	18	20,5	23
b	20	23	28	32	35	39
m	12	16	20	24	27	30
s	22	27	32	36	41	46
l/d1	M 12	M 16	M 20	M 24	M 27	M 30
65	o					
70	o					
75	o	o				
80		o				
85		o				
90		o				
95		o				
100		o	o			
110			o	o		
120			o	o		
130			o	o	o	
140			o	o	o	
150				o	o	
160					o	o
180						o

21 CrMoV57+24CrMo5 Fe

P	1,75	2	2,5	3	3	3,5
d2	8,5	12	15	18	20,5	23
b	20	23	28	32	35	39
m	12	16	20	24	27	30
s	22	27	32	36	41	46
l/d1	M 12	M 16	M 20	M 24	M 27	M 30
65	o					
70	o					
75	o	o				
80		o				
85		o				
90		o				
95		o				
100		o	o			
110			o	o		
120			o	o		
130			o	o	o	
140			o	o	o	
150				o	o	
160					o	o
180						o



