


DIN 787 / DIN 508

DIN 787

~ HRN M.B1.093
~ ISO 299

Vijak za T-utor
Bolts for T-slots
Schrauben für T-nuten




10.9 Br

d1	M 8	M 10	M 12	M 12	M 16	M 16	M 20	M 20	M 24	M 24
e	8	10	12	14	16	18	20	22	24	28
a	13	15	18	22	25	28	32	35	40	44
k	6	6	7	8	9	10	12	14	16	18
l/d1	8x8	10x10	12x12	12x14	16x16	16x18	20x20	20x22	24x24	24x28
32	o									
35		o								
40	o	o	o							
50	o	o	o	o	o					
55			o	o						
60			o	o	o					
63		o				o				
65			o		o					
70			o		o					
80	o		o	o	o		o	o		
100		o	o	o	o	o	o	o	o	o
125			o	o	o	o	o	o		
160					o		o		o	o
200							o	o		
250									o	o

DIN 508

~ ISO 299

Matica za T-utor
Nuts for T-slots
Muttern für T-nuten



10 Br

d1	e	a	h	k	l/d	
M 5	6	10	8	4	5x6	o
M 6	8	13	10	6	6x8	o
M 8	10	15	12	6	8x10	o
M 10	12	18	14	7	10x12	o
M 12	14	22	16	8	12x14	o
M 16	18	28	20	10	16x18	o
M 20	22	35	28	14	20x22	o
M 24	28	44	36	18	24x28	o

