


# DIN 6796 / DIN 6798 A

## DIN 6796

~ HRN M.B2.138  
~ ISO 10670

### Podložna pločica tanjurasta

Conical spring washers for  
bolted connections  
Spannscheiben für Schraubenverbindungen




## DIN 6798 A

~ HRN M.B2.151  
~ UNI 8842

### Zupčasta podložka

Serrated lock washers,  
external teeth  
Fächerscheiben außengezahnt



Br Zn

Br Zn

N	d1	d2	h	s			N	d1	d2	s		
M 3	3,2	7	0,85	0,6	o	o	M 3	3,20	6,00	0,40	o	o
M 4	4,3	9	1,30	1,0	o	o	M 4	4,30	8,00	0,50	o	o
M 5	5,3	11	1,55	1,2	o	o	M 5	5,30	10,00	0,60	o	o
M 6	6,4	14	2,00	1,5	o	o	M 6	6,40	11,00	0,70	o	o
M 8	8,4	18	2,60	2,0	o	o	M 8	8,40	15,00	0,80	o	o
M 10	10,5	23	3,20	2,5	o	o	M 10	10,50	18,00	0,90	o	o
M 12	13,0	29	3,95	3,0	o	o	M 12	13,00	20,50	1,00	o	o
M 14	15,0	35	4,65	3,5	o	o	M 14	15,00	24,00	1,00	o	o
M 16	17,0	39	5,25	4,0	o	o	M 16	17,00	26,00	1,20	o	o
M 20	21,0	45	6,40	5,0	o	o	M 18	19,00	30,00	1,40	o	o
M 24	25,0	56	7,75	6,0	o	o	M 20	21,00	33,00	1,40	o	o
							M 22	23,00	36,00	1,50	o	o
							M 24	25,00	38,00	1,50	o	o
							M 27	28,00	44,00	1,60	o	o
							M 30	31,00	48,00	1,60	o	o

