


# DIN 6797 A / DIN 6799

## DIN 6797 A

~ HRN M.B2.150

~ UNI 3703

Zupčasta podloška s vanjskim  
i unutarnjim nazupčenjem  
Internal / external tooth lock washers  
Zahnscheiben



Br

Zn


N	d1	d2	s	Br	Zn
M 3	3,2	6,0	0,4	o	o
M 4	4,3	8,0	0,5	o	o
M 5	5,3	10,0	0,6	o	o
M 6	6,4	11,0	0,7	o	o
M 8	8,4	15,0	0,8	o	o
M 10	10,5	18,0	0,9	o	o
M 12	13,0	20,5	1,0	o	o
M 14	15,0	24,0	1,0	o	o
M 16	17,0	26,0	1,2	o	o
M 18	19,0	30,0	1,4	o	o
M 20	21,0	33,0	1,4	o	o
M 22	23,0	36,0	1,5	o	o
M 24	25,0	38,0	1,5	o	o
M 27	28,0	44,0	1,6	o	o
M 30	31,0	48,0	1,6	o	o

## DIN 6799

~ HRN M.B2.153

~ UNI 7434

Prstenasti osigurač za osovinice  
Retaining washers for shafts  
Sicherungsscheiben für Wellen



Br

d1	s	d4	a	d2	Br
1,4-2,0	0,30	2,90	1,01	1,2	o
2,0-2,5	0,40	3,90	1,28	1,5	o
2,5-3,5	0,50	4,40	1,61	1,9	o
3,0-4,0	0,60	5,90	1,94	2,3	o
4,0-5,0	0,60	6,90	2,70	3,2	o
5,0-7,0	0,70	8,85	3,34	4	o
6,0-8,0	0,70	10,85	4,11	5	o
7,0-9,0	0,70	11,80	5,26	6	o
8,0-11,0	0,90	13,80	5,84	7	o
9,0-12,0	1,00	15,75	6,52	8	o
10,0-14,0	1,10	18,20	7,63	9	o
11,0-15,0	1,20	19,70	8,32	10	o
13,0-18,0	1,30	22,70	10,45	12	o
16,0-24,0	1,50	28,70	12,61	15	o
20,0-31,0	1,75	36,50	15,92	19	o
25,0-38,0	2,00	43,50	21,88	24	o

