


Vijak matični sa šesterokutnom glavom i finim navojem  
Hexagon head bolts with metric fine pitch thread  
Sechskantschrauben mit Schaft, metrisches Feingewinde



## 8.8 Br

d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
b l < 125	22	26	26	30	30	34	38	42	46
b 125 < l < 200						40	44	48	52
b l > 200									
e	14,38	18,90	18,90	21,10	21,10	24,49	26,75	30,14	33,53
k	5,3	6,4	6,4	7,5	7,5	8,8	10,0	11,5	12,5
s po DIN	13	17	17	19	19	22	24	27	30
s po ISO	13	16	16	18	18	21	24	27	30
l \ d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
30	0								
35	0	0	0						
40	0	0	0	0	0				
45	0	0	0	0	0	0			
50	0	0	0	0	0	0	0		
55	0	0	0	0	0	0	0	0	0
60	0	0	0	0	0	0	0	0	0
65	0	0	0	0	0	0	0	0	0
70	0	0	0	0	0	0	0	0	0
75	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0	0
180			0	0	0	0	0	0	0
190			0	0	0	0	0	0	0
200			0	0	0	0	0	0	0
210			0	0	0	0	0	0	0
220			0	0	0	0	0	0	0
230				0	0	0	0	0	0
240				0	0	0	0	0	0
250				0	0	0	0	0	0
260				0	0	0	0	0	0
280				0	0	0	0	0	0
300				0	0	0	0	0	0



## Vijak matični sa šesterokutnom


glavom i finim navojem

Hexagon head bolts with

metric fine pitch thread

Sechskantschrauben mit

Schaft, metrisches Feingewinde




## 8.8 Br

d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
b l < 125	50	54	60	66				
b 125 < l < 200	56	60	66	72	78	84	90	96
b l > 200	69	73	79	85	91	97	103	109
e	35,72	39,98	45,63	51,28	55,80	61,31	66,96	72,61
k	14	15	17	19	21	23	25	26
s po DIN	32	36	41	46	50	55	60	65
s po ISO	34	36	41	46	50	55	60	65
l \ d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
30								
35								
40								
45								
50								
55								
60	0	0						
65	0	0						
70	0	0						
75	0	0						
80	0	0	0	0				
85	0	0		0				
90	0	0	0	0				
100	0	0	0	0	0	0		
110	0	0	0	0	0	0		
120	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0
190	0	0	0	0	0	0	0	0
200	0	0	0	0	0	0	0	0
210	0	0	0	0	0	0	0	0
220	0	0	0	0	0	0	0	0
230	0	0	0	0	0	0	0	0
240	0	0	0	0	0	0	0	0
250	0	0	0	0	0	0	0	0
260	0	0	0	0	0	0	0	0
280				0	0	0	0	0
300				0	0	0	0	0



Vijak matični sa šesterokutnom glavom i finim navojem  
Hexagon head bolts with metric fine pitch thread  
Sechskantschrauben mit Schaft, metrisches Feingewinde




## 8.8 Zn

d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
b < 125	22	26	26	30	30	34	38	42	46
b 125 < l < 200						40	44	48	52
b > 200									
e	14,38	18,90	18,90	21,10	21,10	24,49	26,75	30,14	33,53
k	5,3	6,4	6,4	7,5	7,5	8,8	10,0	11,5	12,5
s po DIN	13	17	17	19	19	22	24	27	30
s po ISO	13	16	16	18	18	21	24	27	30
l/d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
30	0								
35	0	0	0						
40	0	0	0	0	0				
45	0	0	0	0	0	0			
50	0	0	0	0	0	0	0		
55	0	0	0	0	0	0	0	0	0
60	0	0	0	0	0	0	0	0	0
65	0	0	0	0	0	0	0	0	0
70	0	0	0	0	0	0	0	0	0
75	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0	0
160	0		0	0	0	0	0	0	0
180			0		0	0	0	0	0
190			0		0	0	0	0	0
200			0		0	0	0	0	0
210			0		0	0	0	0	0
220			0		0	0	0	0	0
230					0	0	0	0	0
240					0	0	0	0	0
250					0	0	0	0	0
260					0	0	0	0	0
280					0	0	0	0	0
300					0	0	0		



Vijak matični sa šesterokutnom glavom i finim navojem  
Hexagon head bolts with metric fine pitch thread  
Sechskantschrauben mit Schaft, metrisches Feingewinde




## 8.8 Zn

d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 39 x 3	M 39 x 3	M 42 x 3
b l < 125	50	54	60	66				
b 125 < l < 200	56	60	66	72	78	84	90	96
b l > 200	69	73	79	85	91	97	103	109
e	35,72	39,98	45,63	51,28	55,80	61,31	66,96	72,61
k	14	15	17	19	21	23	25	26
s po DIN	32	36	41	46	50	55	60	65
s po ISO	34	36	41	46	50	55	60	65
l \ d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
30								
35								
40								
45								
50								
55								
60	0							
65	0	0						
70	0	0						
75	0	0						
80	0	0	0	0				
85	0	0		0				
90	0	0	0	0				
100	0	0	0	0	0	0		
110	0	0	0	0	0	0		
120	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0
180	0	0	0	0	0	0	0	0
190	0	0	0	0	0	0	0	0
200	0	0	0	0	0	0	0	0
210	0	0	0	0	0	0	0	0
220	0	0	0	0	0	0	0	0
230	0	0	0	0	0	0	0	0
240	0	0	0	0	0	0	0	0
250	0	0	0	0	0	0	0	0
260	0	0	0	0	0	0	0	0
280				0	0	0	0	0
300				0	0	0	0	0



Vijak matični sa šesterokutnom glavom i finim navojem  
 Hexagon head bolts with metric fine pitch thread  
 Sechskantschrauben mit Schaft, metrisches Feingewinde




## 10.9 Br

d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
b < 125	22	26	26	30	30	34	38	42	46
b 125 < l < 200						40	44	48	52
b > 200									
e	14,38	18,90	18,90	21,10	21,10	24,49	26,75	30,14	33,53
k	5,3	6,4	6,4	7,5	7,5	8,8	10,0	11,5	12,5
s po DIN	13	17	17	19	19	22	24	27	30
s po ISO	13	16	16	18	18	21	24	27	30
l \ d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
30	0								
35	0	0	0						
40	0	0	0	0	0				
45	0	0	0	0	0	0			
50	0	0	0	0	0	0	0		
55	0	0	0	0	0	0	0	0	0
60	0	0	0	0	0	0	0	0	0
65	0	0	0	0	0	0	0	0	0
70	0	0	0	0	0	0	0	0	0
75	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0	0
180		0	0	0	0	0	0	0	0
190			0	0		0	0	0	0
200			0	0		0	0	0	0
210			0	0		0	0	0	0
220			0	0		0	0	0	0
230				0		0	0	0	0
240				0		0	0	0	0
250				0		0	0	0	0
260				0		0	0	0	0
280				0		0	0	0	0
300				0		0	0		



Vijak matični sa šesterokutnom glavom i finim navojem  
Hexagon head bolts with metric fine pitch thread  
Sechskantschrauben mit Schaft, metrisches Feingewinde



## 10.9 Br

d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
b l < 125	50	54	60	66				
b 125 < l < 200	56	60	66	72	78	84	90	96
b l > 200	69	73	79	85	91	97	103	109
e	35,72	39,98	45,63	51,28	55,80	61,31	66,96	72,61
k	14	15	17	19	21	23	25	26
s po DIN	32	36	41	46	50	55	60	65
s po ISO	34	36	41	46	50	55	60	65
l \ d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
30								
35								
40								
45								
50								
55								
60								
65	o	o						
70	o	o						
75	o	o						
80	o	o	o	o				
90	o	o	o	o				
100	o	o	o	o	o	o		
110	o	o	o	o	o	o		
120	o	o	o	o	o	o	o	o
130	o	o	o	o	o	o	o	o
140	o	o	o	o	o	o	o	o
150	o	o	o	o	o	o	o	o
160	o	o	o	o	o	o	o	o
180	o	o	o	o	o	o	o	o
190	o	o	o	o	o	o	o	o
200	o	o	o	o	o	o	o	o
210	o	o	o	o	o	o	o	o
220	o	o	o	o	o	o	o	o
230	o	o	o	o	o	o	o	o
240	o	o	o	o	o	o	o	o
250	o	o	o	o	o	o	o	o
260	o	o	o	o	o	o	o	o
280				o	o	o	o	o
300				o	o	o	o	o



## Vijak matični sa šesterokutnom


glavom i finim navojem

Hexagon head bolts with

metric fine pitch thread

Sechskantschrauben mit

Schaft, metrisches Feingewinde




## 10.9 Zn

d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
b l < 125	22	26	26	30	30	34	38	42	46
b 125 < l < 200						40	44	48	52
b l > 200									
e	14,38	18,90	18,90	21,10	21,10	24,49	26,75	30,14	33,53
k	5,3	6,4	6,4	7,5	7,5	8,8	10,0	11,5	12,5
s po DIN	13	17	17	19	19	22	24	27	30
s po ISO	13	16	16	18	18	21	24	27	30
l d1	M 8 x 1	M 10 x 1	M 10 x 1,25	M 12 x 1,25	M 12 x 1,5	M 14 x 1,5	M 16 x 1,5	M 18 x 1,5	M 20 x 1,5
30	0								
35	0	0	0						
40	0	0	0	0	0				
45	0	0	0	0	0	0			
50	0	0	0	0	0	0	0		
55	0	0	0	0	0	0	0	0	0
60	0	0	0	0	0	0	0	0	0
65	0	0	0	0	0	0	0	0	0
70	0	0	0	0	0	0	0	0	0
75	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0
85	0	0	0	0	0	0	0	0	0
90	0	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0	0
110	0	0	0	0	0	0	0	0	0
120	0	0	0	0	0	0	0	0	0
130	0	0	0	0	0	0	0	0	0
140	0	0	0	0	0	0	0	0	0
150	0	0	0	0	0	0	0	0	0
160	0	0	0	0	0	0	0	0	0
180			0	0	0	0	0	0	0
190			0	0		0	0	0	0
200			0	0		0	0	0	0
210			0	0		0	0	0	0
220			0	0		0	0	0	0
230				0		0	0	0	0
240				0		0	0	0	0
250				0		0	0	0	0
260				0		0	0	0	0
280				0		0	0	0	
300				0		0	0	0	



Vijak matični sa šesterokutnom glavom i finim navojem  
Hexagon head bolts with metric fine pitch thread  
Sechskantschrauben mit Schaft, metrisches Feingewinde



## 10.9 Zn

d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
b l < 125	50	54	60	66				
b 125 < l < 200	56	60	66	72	78	84	90	96
b l > 200	69	73	79	85	91	97	103	109
e	35,72	39,98	45,63	51,28	55,80	61,31	66,96	72,61
k	14	15	17	19	21	23	25	26
s po DIN	32	36	41	46	50	55	60	65
s po ISO	34	36	41	46	50	55	60	65
l \ d1	M 22 x 2	M 24 x 2	M 27 x 2	M 30 x 2	M 33 x 2	M 36 x 3	M 39 x 3	M 42 x 3
30								
35								
40								
45								
50								
55								
60	o							
65	o	o						
70	o	o						
75	o	o						
80	o	o	o	o				
85	o	o	o	o				
90	o	o	o	o				
100	o	o	o	o	o	o		
110	o	o	o	o	o	o		
120	o	o	o	o	o	o	o	o
130	o	o	o	o	o	o	o	o
140	o	o	o	o	o	o	o	o
150	o	o	o	o	o	o	o	o
160	o	o	o	o	o	o	o	o
180	o	o	o	o	o	o	o	o
190	o	o	o	o	o	o	o	o
200	o	o	o	o	o	o	o	o
210	o	o	o	o	o	o	o	o
220	o	o	o	o	o	o	o	o
230	o	o	o	o	o	o	o	o
240	o	o	o	o	o	o	o	o
250	o	o	o	o	o	o	o	o
260	o	o	o	o	o	o	o	o
280				o	o	o	o	o
300				o	o	o	o	o

