

DIV 5005 / DIV 5006

DIV 5005

Turbo vijak
Concrete frame screws



D	Dimenzija vijka	Min. dubina sidrenja	Svrdo	
7,5	42	30-60*	6	o
7,5	52	30-60*	6	o
7,5	62	30-60*	6	o
7,5	72	30-60*	6	o
7,5	92	30-60*	6	o
7,5	112	30-60*	6	o
7,5	132	30-60*	6	o
7,5	152	30-60*	6	o
7,5	182	30-60*	6	o
7,5	202	30-60*	6	o
7,5	212	30-60*	6	o

* OVISNO O TVRDOĆI BAZNOG MATERIJALA

NAPOMENA: U PONUDI IMAMO ŽUTO I BIJELO CINČANE VIJKE

DIV 5006

Turbo vijak s cilindričnom glavom
Concrete frame screws

D	Dimenzija vijka	Min. dubina sidrenja	Svrdo	
7,5	52	30-60*	6	o
7,5	72	30-60*	6	o
7,5	92	30-60*	6	o
7,5	112	30-60*	6	o
7,5	132	30-60*	6	o
7,5	152	30-60*	6	o
7,5	182	30-60*	6	o

* OVISNO O TVRDOĆI BAZNOG MATERIJALA

